

# InnoVet<sup>®</sup> Select HF

HIGH FREQUENCY RADIOGRAPHIC SYSTEM



The  
Professional's  
Choice

**"THE MOST TRUSTED NAME IN VETERINARY RADIOGRAPHY"**

Designed by veterinarians for veterinarians, the InnoVet Select HF has "All the little things in mind" and delivers uncompromising functionality.

## INNOVET MEANS INTEGRITY

InnoVet revolutionized veterinary radiography in 1991 with the first x-ray system designed by veterinarians. Since then, InnoVet has manufactured more than 6,000 veterinary x-ray systems, making it the #1 veterinary x-ray manufacturer in the United States.

Add to that, the industry's best warranty and it's no wonder InnoVet is the most trusted name in veterinary radiography.



## LOCAL SUPPORT

Capital equipment is a long-term investment that deserves personal attention from a service professional who understands your practice.

Regional InnoVet dealers are factory-trained to install and service your x-ray systems with immediate on site and remote support. Our trusted support network means image quality will never slow down your practice.

## INDUSTRY BEST WARRANTY

Our 7-year limited parts warranty secures your investment today and guarantees your investment value tomorrow.

## DIGITAL READY – RIGHT FOR TODAY OR TOMORROW

Our systems are compatible with most digital imaging systems.

# InnoVet®

2901 W. Lawrence Ave. • Chicago, IL 60625  
800-972-9776 • 773-588-2444  
Fax 773-588-3424  
www.innovet4vets.com



## System Specifications

### HIGH FREQUENCY GENERATOR

- 20 KHz High Frequency technology
- 30 kW rating
- Two-point technique selection (kVp, mAs)
- kVp range: 40 – 125, in 1 kV increments
- mA stations: 50s, 100s, 100L, 300L
- Digital kVp, mA, and mAs readout
- Tilt-out control panel
- Built-in tube protection and self diagnostics
- Adjustable volume, audible exposure signal
- Automatic generator "Shut Off" circuit
- Tilt-out control panel
- UL classified

### TABLE / TUBESTAND

- Enclosed, integrated radiographic table
- Stationary table top: 53 in. x 24 in.
- Welded base construction
- Transformer mounting shelf
- Grid cabinet with Simplex cassette tray
- Grid cabinet / tubestand interlock
- Grid 8:1 ratio, 103 LPI
- Animal restraining device
- Angulation dial and deluxe operator handgrips
- Tubestand handles

### X-RAY TUBE

- 1.0-2.0 mm F.S., 140,000 H.U. with 90° horns

### CABLES

- 12 ft. high voltage cables with federal terminations

### COLLIMATOR

- Manual collimator with light field and swivel mount
- Field light "on" time – selectable 30, 60, 90 or 120 seconds
- Radiation leakage well below Federal standards for human medical systems

## System Options

- Anatomical programmed technique selection
- 500 mA generator upgrade
- Two-way float top table, 58 in. x 32 in.
- Four-way float top table, 67 in. x 32 in.
- Table top fluid trough
- "Hands-free" collimator light system



5325 Louie Lane Suite 1 Reno, NV 89511  
800-300-XRAY (9729)  
sales@abi-ess.com